# artec 300 series



# ARTEC-306-W



#### **DESCRIPTION**

The ARTEC-306-W 2-way passive full range loudspeaker utilizes a 6" low frequency transducer and the M-26 compression driver. The cabinet manufactured using top quality of Birch plywood and finished with a durable white paint finish. Thanks to its small size, it is ideal for venues with low ceilings, or limited space.

The Artec-300 cabinets are constructed from Baltic Birch plywood and finished with a durable ISO-flex paint. The trapezoidal enclosure design helps eliminate standing wave coloration and at the same time, permits close-packed horizontal or vertical arrays.

A rotatable horn allows the systems to be installed in either the vertical or horizontal position maintaining the needed dispersion characteristics. The cabinet is delivered with a U-bracket mount.

#### **KEY FEATURES**

- ·1 x 6B low frequency loudspeaker
- ·1 x M-26 compression driver
- · Rotatable 90° x 60° horn
- · Vertical or horizontal positioning
- · VESA75/VESA100 standard threaded mounting points
- · AXU-A306-W U-Bracket included

#### **APPLICATIONS**

- · A/V systems and corporate events
- · Meeting rooms, classrooms, and exhibit areas
- · Installations in bars and clubs

#### **SPECIFICATIONS**

Performance	
Frequency Range (-10 dB)	70 Hz - 20 kHz
Horizontal Coverage (-6 dB)	90°
Vertical Coverage	60°
Nominal Impedance	8 ohms
RMS Power Handling	100 W
Peak Power Handling	400 W
On-axis Sensitivity 1W/1 m	90 dB SPL
Maximum Peak SPL at 1 m	116 dB
Recommended Amplifier	PA-900
Recommended Processor	DSP-226
Connectors Audio Input Connector	Covered Barrier Strip Terminals
Audio Output Connector	Covered Barrier Strip Terminals
Enclosure	
Enclosure Construction	Birch Plywood
Enclosure Geometry	Trapezoidal
Rigging	M10 Rigging Points
Finish	ISO-flex Paint
Color	White
Color — Depth	White 260 mm (10,2 in)
	,



# ARTEC-306-W

### Components

Shipping Weight

LF Driver	6B
HF Driver	M-26
Horn/Waveguide	BCT-96
Shipping	
Carton Dimensions ( H x W x D )	471 x 266 x 330 mm 18,5 x 10,5 x 13,0 in

9,2 kg ( 20,3 lb )

## **ORDERING INFORMATION**

Performance			
Model	Description	P/N	
System			
ARTEC-306-W	2-way Passive Point Source	10423851	
Replacement Parts			
6B	Cone Transducer	20208260	
BCT-96	Horn	30006201	
F-ACT8	Filter	30005424	
GM-M26	Diaphragm	20205050	
LAMP-F-18	Lamp	30000536	
M-26	Compression Driver	10207070	
Accessories			
ANL-2	Rigging Accessories	10101020	
AX-SPG1	Installation & Stacking Acc.	10105050	
AXC-AT	Installation & Stacking Acc.	10104310	
AXR-AR5-W	Installation & Stacking Acc.	10104880	
AXW-3-W	Installation & Stacking Acc.	10104860	

## **DIMENSIONS**









